

WASH UP SINK WITH KNEE VALVE OPERATION SYSTEM & BRACKET SUPPORTS



SPECIFICATIONS:

- BODY:**
STAINLESS STEEL TYPE 304 #14 GA (0.0781") BRUSH FINISH.
- BOWL:**
ONE BOWL WELDED 3/4" RADIUS CORNERS, PITCHED TO DRAIN HOLE 3-1/2" OF DIAMETER
- BACKSPLASH:**
10" HEIGHT X 2" RECESS WITH 45° SLOPE AT TOP.
- SUPPORT:** 3 STAINLESS STEEL BRACKETS 8"x11"x1-5/8" AT STUD WALL OR BLOCKING WITH 3 SCREWS
- FAUCET LOCATION**
ONE HOLE AT BACKSPLASH DIAMETER 7/8" PER PLANS, WITH STAINLESS STEEL KNEE VALVE BRACKET 12GA WELDED TO BASE TUB.
- INSTALLATION AT WALL:**
3 CLIPS OF 3"x4" STAINLESS STEEL 14 GAUGE (0.0781") MINIMUM AND ONE CLIP @16 INCHES ON CENTERS INCLUDED AT STUD WALL OR BLOCKING
- 1 (ONE) MIXING VALVE MODEL BSMV1001 EACH SINK
- 1 (ONE) KNEE VALVE MODEL BSMAA2003 EACH FAUCET

AVAILABLE SAME MODELS WITH LEGS OR ROUND BRACKETS SUPPORT.

CONTACT US FOR ANY PRICE OR SIZE QUESTION. AND REMEMBER WE ALSO WORK WITH CUSTOM MADE SINKS

TABLE: KNEE VALVE OPERATION (ALL DIMENSIONS IN INCHES)							
MODEL	GENERAL		BOWL	FAUCETS	KNEE VALVES	SOAP DISP.	MIXING VALVE
	L1	W1	L x W x D				
020WK20208BS	20	20	17-1/4X16-5/8X8	1	1	1	1
020WK24208BS	24	20	21-1/4X16-5/8X8	1	1	1	1
021WK36208BS	36	20	33-1/4X16-5/8X8	1	1	1	1
0S2WK36208BS	36	20	33-1/4X16-5/8X8	2	2	1	1
022WK40208BS	40	20	37-1/4X16-5/8X8	2	2	1	1
022WK42208BS	42	20	39-1/4X16-5/8X8	2	2	1	1
022WK48208BS	48	20	45-1/4X16-5/8X8	2	2	1	1
024WK60208BS	60	20	57-1/4X16-5/8X8	3	3	2	1
024WK72208BS	72	20	69-1/4X16-5/8X8	3	3	2	1
024WK80208BS	80	20	77-1/4X16-5/8X8	4	4	3	1
025WK84208BS	84	20	81-1/4X16-5/8X8	4	4	3	1
026WK96208BS	96	20	93-1/4X16-5/8X8	4	4	3	1
027WK100208BS	100	20	97-1/4X16-5/8X8	5	5	4	1
028WK108208BS	108	20	105-1/4X16-5/8X8	5	5	4	1
029WK120208BS	120	20	117-1/4X16-5/8X8	5	5	4	1
030WK144208BS	144	20	141-1/4X16-5/8X8	6	6	5	1
CUSTOM	PLEASE SEND US AN E-MAIL OR CALL						



DRAIN MODEL: BSM-AA-140



FAUCET MODEL: BSM-515



KNEE VALVE MODEL: BSMAA 2003



MIXING VALVE MODEL: BSMV 1001



SOAP DISPENSER MODEL: BSM-590

